



SurLok Plus™

The SurLok Plus™ compression lug is a field installable, highly reliable alternative to common compression lugs. Using industry standard crimp, screw, and busbar termination options, thus eliminating the need to purchase special torque tools.

Amphenol's SurLok Plus™ is an environmentally sealed version of our original SurLok™ but available in smaller sizes, and features a quick lock and press-to-release design. Incorporating the latest R4 RADSOK® Technology, SurLok Plus™ is a compact, quick mating, and robust product line.

The RADSOK® high amperage contact technology utilizes high tensile strength properties of a stamped and formed, high conductivity alloy grid to produce low insertion forces while maintaining a large conductive surface area.

The R4 version of the RADSOK® represents the culmination of three years of research and development in laser welding copper based alloys.

Features:


- R4 RADSOK® Technology
- IP67 rated
- Touch Proof
- Quick lock and press-to-release design
- "Keyway" design to prevent incorrect mating
- 360° rotating plug
- Various termination options (Threaded, Crimp, Busbar)
- Compact robust design




Technical Data			
Contact Size	5.7mm (120A) 8.0mm (200A) 10.3mm (300A)	IP Rating	IP 67
Current Rating	120A~300A	Protection	Touch Proof
Operating Voltage	1000V AC/DC	Flammability	UL 94-V0
Operating Temp	-40°C to 125°C	Locking	Spring Locking

The markets and applications for the SurLok Plus™ series include but are not limited to the following:


- EV/HEV
- BMS/Energy Storage
- Medical
- Rail Mass Transit
- Process Control/Automation
- Heavy Equipment




Size	Screw Termination		
	A	B	C
5.7mm	16	37.7	1
8.0mm	19	46.2	1
10.3mm	25.8	55.9	0.3




Size	Crimp Termination		
	A	B	C
5.7mm	16	40.7	1
8.0mm	19	53.7	1
10.3mm	25.8	69.2	0.3




Size	Busbar Termination		
	A	B	C
5.7mm	16	47.6	1
8.0mm	19	62.2	1
10.3mm	43	68.8	0.3



Size	Plug Dimensions			
	A	B	C	D
5.7mm	22.6	58.8	30	18
8.0mm	29	75.6	38.6	21.6
10.3mm	40.5	88.5	42.5	30.3



Size	Plug Dimensions			
	A	B	C	D
8.0mm	24.6	72.4	34.8	21.4



Size	Press-Fit Termination				
	A	B	C	D	E
5.7mm	16	32.8	27.7	5.1	3±0.3

	Product Series: SurLok Plus™		RADSOK® Size	Applicable Cable Size		Backshells		Sealing		Connector Color		Keyway (Omit for no Keyway)	EMI	HVIL												
	PLUG	Plug		5.7mm	8.0mm	B	W/ Backshells	S	IP67 Sealed (W/ Grommet & O-Rings)	O	Orange															
	SLP	P Right Angle Plug 90°	A	5.7mm	16	16mm² : 100 Amps	B	W/ Backshells	S	IP67 Sealed (W/ Grommet & O-Rings)	O	Orange	0	90°	Note: Please select both EMI and HVIL or none											
				25	25mm² : 120 Amps	N										W/O Backshells (For Overmolding Only)	N	Non-Sealed	R	Red	1	180° (W/O EMI & HVIL)				
				35	35mm² : 150 Amps																		E	EMI	H	HVIL
				50	50mm² : 200 Amps																					
				IP Straight Plug	C	10.3mm										70	70mm² : 250 Amps	N	W/O Backshells (For Overmolding Only)	N			Non-Sealed	R	Red	2
		85	85mm² : 350 Amps																							
		12	120mm² : 400 Amps																							
		14	185mm² : 500 Amps																							
		18	185mm² : 500 Amps																							

	Product Series: SurLok Plus™		RADSOK® Size	Applicable Cable Size (for Crimping Termination only)		Termination Style		Panel Mount	Sealing		Connector Color		Keyway (Omit for no Keyway)	EMI	HVIL													
	RECEPTACLE	Receptacle		5.7mm	8.0mm	B	Busbar		P	Panel Mount W/ Flange	S	IP67 Sealed (W/ Grommet & O-Rings)				O	Orange											
	SLP	R Right Angle Receptacle 90° (W/O Keyway)	A	5.7mm	16	16mm² : 100 Amps	B	Busbar	S	IP67 Sealed (W/ Grommet & O-Rings)	O	Orange	0	90°	Note: Please select both EMI and HVIL or none													
				25	25mm² : 120 Amps	T										Threaded Post	N	W/O Flange	N	Non-Sealed	R	Red	1	180° (W/O EMI & HVIL)				
				35	35mm² : 150 Amps																				E	EMI	H	HVIL
				50	50mm² : 200 Amps																							
				IR Straight Receptacle (W/ Keyway)	C	10.3mm										70	70mm² : 250 Amps	C	Crimp	N	W/O Flange	N			Non-Sealed	R	Red	2
		85	85mm² : 350 Amps																									
		12	120mm² : 400 Amps																									
		14	185mm² : 500 Amps																									
		18	185mm² : 500 Amps																									

Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

For further information on your individual application requirements, contact: Amphenol Corporation

North America:
Amphenol Industrial Operations
180 N. Freeport Drive, Plant 4
Nogales, AZ 85621
Tel: (888) 364-9011
Fax: (520) 285-5134

Europe:
Amphenol Industrial Operations Europe
Via Barbaiana 5
1-20020 Lainate (MI) Italy
Tel: +39 02 93254.204
Fax: +39 02 93254.444

Middle East:
Amphenol Middle East Enterprises FZE
Office C-37 PO Box 21107
Ajman Free Zone, UAE
Tel: +9 716-7422494
Fax: +9 716-7422941

Asia:
Amphenol Technology (Zhuhai) Co., Ltd.
No. 63 Xing Han Road, San Zao Town
Jin Wan District, Zhuhai City, China 519040
Tel: +86 756-3989760
Fax: +86 756-3989768

Email: tech@amphenol-aio.com

Email: info@amphenol-aio.com

Email: jhussain@amphenol-industrial.com

Email: enquiry@amphenol-aio.com